

HYLOMAR[®]

THE original UNIVERSAL JOINTING COMPOUND

M

- Non-setting jointing compound.
- Temperature range -50°C to $+250^{\circ}\text{C}$.
- Resistant to fuels, oils, coolants and gases.
- Specified worldwide by original equipment manufacturers for over 40 years.
- Hylomar Ltd - The ONLY manufacturer of Hylomar[®].



[®]**HYLOMAR**

THE original UNIVERSAL JOINTING COMPOUND

M

- Easy to use.
- Unlimited assembly time.
- Easy to disassemble components sealed with Hylomar.
- Use on metal to metal joint surfaces to replace conventional pre-formed gaskets.
- Use as a gasket dressing to improve the sealing performance of the gasket and to assist gasket alignment during assembly.
- Use as a non-curing thread sealant.
- Resists vibration.
- Approved for use in the following industries: automotive engines, transmissions, motor cycle engines, power generation, electric motors, pump manufacture, valve manufacturing, refineries, tractors, chemical, mining, marine engines, railways, paper and packaging machinery and non-aerospace defence industries.
- The Hylomar products for aerospace applications are either Hylomar Aerograde or Aerograde Ultra.

HYLOMAR M IS AVAILABLE IN FOLLOWING FORMATS

- TUBE 40 ml (12 pcs/case)
- TUBE 80 ml (10 pcs/case)
- AEROSOL 200 ml (12 pcs/case)
- BRUSH TOP TIN 250 ml (12 pcs/case)
- CARTRIDGE 300 ml (12 pcs/case)
- TIN 1000 ml (10 pcs/case)

ANTWERP LION OIL WORKS N.V.
VLAAMSEKAAI 2-5 B-2000 Antwerpen
T.: +32 (0)3 237 00 45 www.lionoil.be