G3P

20120228

ELECTRICAL PUMPS G3 OIL/GREASE PUMP

G3 ELECTRIC PUMP

With its flexible design, including adjustable pump elements and ability to work with both injector-based and series progressive systems, G3 is a rugged, cost-effective pump designed to serve multiple markets and applications. The new pump features 3 control choices, which means added flexibility for easy lube system setup, operation and troubleshooting. The pump extends machinery life, reduces operating costs and increases productivity for usage in a wide varietv of markets. including in-plant manufacturing, mobile on-road and off-road, and wind turbines.

Specifications

Lubricant

Maximal working pressure Power

Number of pump elements - type of element - max. flow / element Reservoir sizes Operating temperature Protection degree 350 bar 12 or 24 VDC 90-240 VAC 1 to 3 adjustable output 2, 3 or 4 cc/min. 2,4,8,12 or 16 liter -25° to 70°C IP69K

Oil or grease,

max. NLGI 2

Ordering references

G3S

Features	G3S	G3P	G3M
Internal controller	-		
Low level indicator	-		
Pump on / pump off timer	-		
Pre-lube function	-		
Manual run	-		
Password protection	-		
Machine count input	-	-	
Up to three pressure / cycle switch inputs	-	-	

service

G3M

contact us for more information info@lionoil.be









systems

fluids



parts